

**TRY BEFORE  
YOU BUY**

**TESTING LAB**



- Choose the most suitable equipment.
- Test your own material.
- Touch the result with your own hands.

# PMG 1200 H

## HYDRAULIC DRIVE PRE-SHREDDER

PMG pre-shredders, with high cutting efficiency, have been designed to reduce the size of different materials.

Production can be improved by choosing the appropriate grid for each specific material.



Cutting chamber  
heavy duty and easy to replace blades.

Hydraulic pusher  
to ensure constant feeding.

Manufactured in accordance to CE rules

EXAMPLES OF PROCESSED MATERIAL (INPUT / OUTPUT)



TECHNICAL SPECIFICATIONS

- | Loading hopper: 1000 x 1590 mm
- | Rotordiameter: 400mm
- | Pusherstroke: 500 mm
- | Screen sizes: Ø 10-12-15-20-25-30-40-50 mm
- | Number of rotating blades: 47
- | Number of external blades: 4
- | Number of counter-blades: 2
- | Drive type: Hydraulic
- | Installed power: 93 kW - 142 A
- | Voltage (standard): 380 V - 50 Hz
- | Total weight: 6715 kg - 1700 kg [\*]
- | Hydraulic oil tank capacity: 130 liters
- | Noise level (not loaded): 84 db(A)

[\*]Referring to the hydraulic unit

